

Features

1. Cylinders comply to ASME B-30.1. High strength alloy steel for safety and durability
2. Inside cylinder treated to enhance durability
3. Collar threads, plunger threads and base mounting holes enable easy fixture
4. Heavy duty plunger spring return
5. High quality 3/8-18NPT quick coupling
6. Baked enamel finish on both cylinder and pump for increased corrosion resistance
7. Pump has internal pressure relief valve for overload protection
8. Gauge is stainless steel for durability



Set Inclusions

Product Code	PSC55KIT	PSC102KIT	PSC106KIT	PSC1010KIT	PSC154KIT	PSC156KIT	PSC252KIT	PSC254KIT	PSC256KIT	PSC2514KIT	PSC506KIT
Cylinder tonne/stroke mm	5/127	10/54	10/156	10/257	15/102	15/152	25/51	25/102	25/159	25/362	50/159
Pump	PHP002 Dual Speed Hand Pump 3/8NPTF									PHP004 Dual Speed Hand Pump 3/8NPTF	
Hose	PAA018 1.8M Thermoplastic 4:1 SAFETY FACTOR										
Gauge	PAB101 700 bar 100MM Diametre Stainless Steel Gauge										
Gauge Adapter	PAC101 700 bar Gauge Adapter										
Kit Weight kg	9	9.3	11.4	13.4	12	13.8	13.4	15.2	17	24.7	30.2

*Other sets available on request

**See individual product pages for further specifications

The information contained in this brochure is to be used as a guide only, specifications are subject to change without notice.